



SHOWROOM FX

Application Guidelines for Interior/Exterior

EXTERIOR APPLICATION

Suggested Products

Clay Magic® Kit
ShowroomFX Tire & Wheel Cleaner
ShowroomFX Natural Big Orange degreaser
Meguiars M105/Menzerna Polish
ShowroomFX Acrylic Paint Sealant
ShowroomFX Plastic Cleaner/Polish
ShowroomFX Car Wash Concentrate
ShowroomFX Tire and Rubber Dressing
ShowroomFX Metal Polish

Suggested Microfiber/Foam

“ShMITT” Foam Wash Mitt
Waffle Weave Drying Towel
Applicator Pad-Oval Blue foam or 4” round blue foam
“Super Plush” Polish Towel
4” round Tire Dress Applicator
Gray Plush Microfiber Detail Towel
Blue Orbital Polish Bonnet

SURFACE PREPARATION

- Wash surface with Car Wash Concentrate to remove heavy dirt and soil. Rinse surface clean. Use Clay Magic® bar to remove all surface contaminants prior to initial application or as needed. Wipe the surface with a 50/50 solution of isopropyl alcohol and distilled water to remove any remaining residue prior to the ShowroomFX product application. Acrylic Paint Sealant (APS) works best on clean, wax-free surfaces. For future maintenance, use several capfuls of the Car Wash Concentrate with a suitable non-scratching wash mitt.
- Clean wheels and tires with the Wheel & Tire Cleaner, rinse thoroughly. For use polished aluminum or chrome wheels, the car wash concentrate and water is sufficient to clean these surfaces. Dry with Waffle Weave drying towel for worry-free drying. We recommend using Metal Polish to make those uncoated aluminum wheels sparkle after washing.
- HELPFUL HINT: Use Natural Big Orange to remove bug and adhesive residue, tar and grease from the paint surface.

- We recommend using Meguiars M105, Menzerna polishes, or Meguiars M205 to reduce swirl marks and fine scratches. It may be either applied by hand or machine. For hand use, apply the product using a moistened foam polish applicator thoroughly working into the surface until completely broken down. Wipe off remaining residue. Repeat as necessary. When using the Meg with the Porter Cable buffer equipped with the Lake Country Mfg. CCS orange or white foam pad, set your dial between speed 4 and 5. Move in a slow and smooth motion across the surface at the rate of about 1" inch/second. For additional information, refer to our Safety Tips Sheet for Porter Cable/FLEX Buffers listed on the site. This action will allow the buffer to sufficiently break down the product into the paint surface. Work the product until very little residue remains or disappears. Several passes with the buffer may be necessary for desired results. These polishing products produce effective results and prepare the surface for the non-abrasive sealant or waxes. Use detail spray or a 50/50 mixture of isopropyl alcohol and water to remove remaining residue.

POLISH APPLICATION & REMOVAL

- Apply Acrylic Paint Sealant (APS) with dampened applicator pad by hand or with random orbital buffer using a soft blue foam pad to wax-free painted and/or metal surfaces. Quick drying/curing formula allows you to apply a second application to insure even coverage.
- Remove hazed residue with the blue "Super Plush" polish towel or blue orbital polish bonnet over the orange foam pad on your buffer. Allow one hour in between additional product applications. Use the Detail Spray for light clean ups of after washing to help extend the surface protection. Future product applications will apply and remove even easier. Use APS on your wheels to help reduce brake dust build-up.
- Allow longer drying time in humid or cooler weather.

ADDITIONAL EXTERIOR PRODUCT HELPFUL HINTS

- Use the Glass Cleaner with clean woven glass cleaning or microfiber detail towel to ensure streak-free windows.
- Apply Tire and Rubber Dressing for that finishing touch using our 4" round tire dress applicator.
- Use Plastic Cleaner/Polish on headlights, tail lights, and other exterior clear plastic surfaces to remove ultra-fine scratches and dulling haze. Hand or machine use.

INTERIOR APPLICATION

Suggested Products

ShowroomFX Natural Big Orange
 ShowroomFX Plastic Cleaner/Polish
 ShowroomFX Leather/Vinyl/Fabric Cleaner
 ShowroomFX Glass Cleaner
 ShowroomFX Leather Conditioner
 Applicator Pad-Oval Blue foam
 ShowroomFX Leather/Vinyl Dressing
 Microfiber "Super Plush" Polishing Towel
 Woven Glass Cleaning Towel

- Use Natural Big Orange for removing grease and tar. Test in an inconspicuous area.

- Start with Leather/Vinyl/Fabric Cleaner. Safely and effectively cleans this range of surfaces. After cleaning, apply Leather Conditioner to surfaces with applicator pad or by hands. No buffing necessary. Keeps leather soft and moisturized. Reapply as desired.
- Use Leather/Vinyl Dressing for that final touch. Leaves a rich even glow.
- Use Plastic Cleaner/Polish on gauge faces and plastic windows. Excellent for use on carbon fiber and Lexan® surfaces. Safely remove ultra fine scratches and dull haze.
- Use the Glass Cleaner with our woven glass cleaning towel to clean interior windows. Glass Cleaner is safe on tinted windows with its ammonia-free formula.

We recommend using our microfiber towels and foam applicators. Wash microfiber towels and applicators separately from other lint-producing fabrics. Wash in hot water with liquid detergent which contains no bleach or fabric softeners. Hot water wash effectively releases the polish or wax residues trapped in the fibers. Use cold water rinse and add one Tablespoon distilled white vinegar for each microfiber item to release all detergents from the fabrics. Use cool/air fluff dryer setting or line dry to prevent shrinking or static cling.

We value your feedback. Feel free to contact us anytime.

Thank you from Showroom FX.

Showroom FX

PO Box 885

Allen TX 75013

Toll-Free (866) 341-0050 or DFW Local (972) 743-9443

www.showroomfx.com